

अल्पकालीन कोटेशन आमंत्रण सूचना-सं0-02/BIADA/2017-18

औद्योगिक क्षेत्र, पाटलीपुत्रा में अवस्थित कार्यालय के आंशिक मरम्मत का कार्य हेतु कोटेशन आमंत्रित किया जाता है। यह कोटेशन कार्यपालक अभियंता, बियाडा पटना, प्रथम तल उद्योग भवन, पूर्वी गाँधी मैदान के कार्यालय में दिनांक 21.06.2017 के अपराह्न 3:00 बजे तक प्राप्त किया जाएगा तथा दिनांक 21.06.2017 के 3:30 बजे अपराह्न में कोटेशनदाताओं या उनके अधिकृत प्रतिनिधियों के समक्ष तकनीकी बीड एवं वित्तीय बीड खोला जाएगा।

कार्य की विवरणी

Name of Work:- Repair of Area office Building at I/A Patliputra,Patna..						
Sl.No	Discription of items	Unit	Quantity	Rate		Amount
				In Word	In Figure	
1	Removing dry or oil bound distemper by scraping,sand paper and preparing the surface smooth including necessary repair scratches tec. Complete.	sqm	227.32			
2	Demolishing R.C.C work including stacking of steel bars and disposal of unserviceable material withing 50 meters lead:	Cum	0.715			
3	Demolishing brick work including stacking of serviceable material and disposal of unserviceable material within 50 meters lead.					
	In cement mortar.	Cum	1.09			
4	Dismantling doors windows and clerestory windows(steel or wood)shutter including chaukhats,architrage,holdfasts etc.complete and stacking within 50 metres lead.					
	of area 3 sqm and below.	Each	5.000			
5	Brick work with bricks of class designation 100A in superstructure Cement mortar 1:4(1 cement : 4 coarse sand)	Cum	1.93			
6	Providing designation 100 A one brick on flat soling joints filled with local sand including cost of watering, taxes, royalty all complete as per building spoeification and direction of E/I	sqm	49.22			
7	Supplying and filling in plinth with local sand under floors including, watering, ramming consolidating and dressing complete.	Cum	4.86			
8	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering-All work up to plinth level:					
	:1.5:3 (1 Cement: 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size)	Cum	8.03			
9	Providing and laying in position specified grade of Reinforced cement concrete work excluding cost of centring, shuttering, finisnin and reinforcement.All work up to plinth level.					
	1:1:5:3 (1 cement :1.5 coarse sand 0.3 graded stone aggregate 20mm nominal size)	Cum	0.184			

10	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sqm and under including cutting the patch in proper shape and preparing and plastering the surface of the walls complete including disposal of rubbish to the dumping ground wuthin 50 metres lead.					
	with cement mortar 1:4(1 cement:4 coarse sand)	Sqm	18.56			
11	Cement plaster in course sand 12 mm Cement plaster of mix. 1:4 (1 cement : 4 coarse sand)	Sqm	18.42			
12	Reinforcement for RCC. Work including starightening, cutting,bending,placing in position and binding all complete					
	Thermo-Mechanically Treated bars TMTC-500-8 mm dia	Kg	15.00			
13	Providing and applying plaster of paris putty of 2 mm thickness over plastered over surface to prepare the surface even and smooth complete.	sqm	120.65			
14	Distemping with oil bound washable distemper of approved brand and manufacture to give an even shade. New work (two or more coats)over and including priming coat with cement primer.	sqm	111.80			
15	Finishing walls with water proofing cement paint of approved brand and manufacture and of required shade to give an even shade.New work (three or more coats).	Sqm	187.98			
16	Painting with ready mixed paint of approved brand and manufacture in all shades to give an even shade:					
	New steel work (two or more coats)	Sqm	9.70			
	Old steel work(one or more coats)	Sqm	21.61			
	Old wood work(one or more coats)	Sqm	7.94			
17	Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures complete					
	10 litre capacity - White	Each	1.00			
18	Providing and fixing PVC waste pipe for sink or wash basin including PVC waste fittings.					
	Flexible pipe(32 mm dia)	Each	2.00			
19	Providing and fixing brass bib cock of approved quality. 15 mm nominal bore					
	15 mm nominal bore.	Each	4.00			
20	Providing and fixing brass stop cock of approved quality.					
	15 mm nominal bore.	Each	3.00			
21	Provding and fixing 600X450mm beveled edge mirror of superior glass complete with 6mm thick hard board ground fixed to wooden cieats with CP	Each	1.00			

	brass screws & washers complete.					
22	Providing and fixing 50 mm bright finished brass cup board or wardrobe knob of approved quality with.	Each	10.00			
23	Providing and fixing bright finished brass handles with screws etc.complete:					
	100 mm	Each	3.00			
	75 mm	Each	8.00			
24	Repair and polish of sofa set & chair all complete.	Each	9.00			
25	Providing and fixing M.S grill of required patterns in frames of window etc. with MS flats, square or round bars etc. all complete.					
	Fixed to Steel window by welding	Kg	104.06			
26	Providing and fixing anodized aluminum work for doors, windows, ventilators and partitions with extruded built up standard tubular and other sections of approved make conforming to IS:733 and IS:1285, anodized transparent or dyed to required shade according to IS:1868 (Minimum anodic coating of grade AC 15), fixed with rawl plugs and screws or with fixing clips, or with expansion hold fasteners including necessary filling up of gaps at junctions, at top, bottom and sides with required PVC/neoprene felt etc. Aluminum sections shall be smooth, rust free, straight, mitered and jointed mechanically wherever required including cleat angle. Aluminum snap beading for glazing / panelling, C.P brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing and panelling to be paid for separately):					
	Anodised aluminium(anodised transparent or dyed to required shade according to IS:1868,minimum anodic coating of grade AC 15	Kg	29.04			
27	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber/neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item):					
	With float glass panes of 5.50 mm thickness.	sqm	4.84			
28	Supplying plastic chairs midium high back manufacture by supprime,cello,national or equalant	Each	6.00			
29	Wiring for light point/fan point/ exhaust fan point/call bell point with 1.5 sq.mm FR PVC insulated copper conductor single core cable in surface/ recessed medium class PVC conduit with modular switch, modular plate suitable GI box etc. as required.	Point	10.00			
30	Wiring for circuit/Submain wiring along with earth wire with the following sizes of					

